



WILLAMETTE SPA SERVICE, INC.
31100 S.W. UNGER RD.
CORNELIUS, OR 97113
(503) 628-1037

SCOTT'S NO BRAINER GUIDE TO SPA CARE

1. Test clean & fresh water with test strip for Ph and total alkalinity (t.a.) Add Spa Up or baking soda (sodium bicarbonate) to raise the Ph and t.a. to proper level. Proper level for Ph is 7.2 - 7.6, t.a. is 100-150 ppm, for bromine 3-6 ppm, for chlorine 3-5 ppm.
2. Add chlorine or bromine power/granuals (usually the manufacturer has the proper amount to add on their container), about 2 teaspoons in 400 gal.
Note: Use of bromine or chlorine tablets may cause corrosive damage to jets, heater or pump seals.
3. Add spa shock (non-chlorinated) at the proper amount for the number of gallons of your spa. (About 1 oz.)
4. Add 2 oz. of Brite & Clear.
Note: Only add Brite & Clear spa shock at the same time when treating **fresh** water. Spa shock and Brite & Clear should be added every week by alternating one week with spa shock, the next week with Brite & Clear, but **never at the same time except with clean, fresh water.**
5. Operate filter cycle 6-8 hours per day.

WEEKLY:

Test water for Ph, t.a., bromine or chlorine. Adjust as necessary, rinse filter off with hose and sprayer.

MONTHLY:

Clean filter with filter cleaner or a solution of 1 cup of automatic dishwasher soap in 5 gallons of hot water & soak at least 4 hours (overnight is better). A good suggestion here is to have double filters, so that some are being used while some are drying to be installed when the monthly cleaning time is due.

3-6 MONTHS:

Depending on the amount of use and the number of bathers, change the water. The more bathers, or bathers not in the household, means the water must be changed every 90 days. More often is highly recommended.

1 YEAR:

Thorough cleaning. Spa can be cleaned with the same strength solution of 1 cup automatic dishwasher soap and 5 gal. water. Use a scrub sponge made for non-stick surfaces (Teflon). Liquid automatic dishwashing soap can be used full strength when applied to a sponge, also. Covers can be cleaned in the same way.

Thoroughly rinse sides into footwell area and drain. Do this 3 times and refill. Start cycle over again.

ENJOY!!